


JKL LAMP PART NO. (REF.)	COLOR WHITE 4200°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20137-26B	x = .372 y = .371	1125 @ 0°C	320	5	42,000 ± 15%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION				
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE A	FSCM NO. 55335	DRAWING NO. BF20137-26B	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 2/23/05	REVISION DATE 7/30/09	
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO. A	SHEET 1 OF 1		