

Switching device combination - CBL-RBTM-TT - 2701462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Measurement system for load characteristics and bending moments in rotor blades of wind turbine generators. Proactive rotor blade monitoring, early detection of damage, and optimized load control. Reliable in harsh ambient conditions and suitable for remote service.



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356755405

Technical data

General data

Housing material	Sheet steel (dip-primed, powder-coated on the outside, textured finish)
Material cover/door	Sheet steel (with all round PU foam seal, dip-primed, powder-coated on the outside, textured finish)
RAL color	7035 light grey
Weight	12.6 kg
Installation location	Interior (wind turbine generator)
Degree of protection	IP65
Protection class	I, IEC 61140, EN 61140, VDE 0140-1

Housing

Housing material	Sheet steel (dip-primed, powder-coated on the outside, textured finish)
Material cover/door	Sheet steel (with all round PU foam seal, dip-primed, powder-coated on the outside, textured finish)
RAL color	7035 light grey

Ambient conditions

Ambient temperature (operation)	-25 °C ... 45 °C
Ambient temperature (storage/transport)	-35 °C ... 45 °C
Shock (operation)	30g

Switching device combination - CBL-RBTM-TT - 2701462

Technical data

Ambient conditions

Shock (storage/transport) GRP	30g
Vibration (operation)	2.3g

Dimensions

Outer dimensions: width, height, depth	380 mm x 380 mm x 210 mm (without housing feed-throughs)
	334 mm x 355 mm x 2 mm (Mounting plate dimensions)

Technical characteristics

Nominal power	approx. 69 W (for 230 V AC)
	approx. 14.4 W (at 24 V DC)
Nominal current I _N	approx. 0.3 A (for 230 V AC)
	approx. 6 A (at 120 V AC)
	approx. 0.6 A (at 24 V DC)
Nominal voltage U _N	230 V AC (1/N/PE)
Output voltage	24 V DC
Control voltage	24 V DC
Protection	500 mA (normal blow)

Cable entry

Type of cable entry	Coupling
	Cable gland

Standards and Regulations

Vibration (operation)	2.3g
Shock (operation)	30g

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>