

## Specification Sheet

Part Number: 157-00216



Offset Fir Tree Cable Tie, 12.5mm Offset, 9.2" Long, .24-.27" Hole, 50lb, PA66HIRHS, Black, 1000/pkg

Article Number	157-00216
Type	T50ROSFT612.5SO
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes.</li><li>•The 'disc' on the top of the fir tree covers the hole and minimises the ingress of water and dirt.</li></ul>
Quantity Per	carton

### Product Description

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

<b>Short Description</b>	Offset Fir Tree Cable Tie, 12.5mm Offset, 9.2" Long, .24-.27" Hole, 50lb, PA66HIRHS, Black,1000/pkg
<b>Global Part Name</b>	T50ROSFT612.5SO-PA66HIRHS-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	222.0
<b>Length L (Imperial)</b>	9.2
<b>Length L (Metric)</b>	234.2
<b>Offset Length(Imperial)</b>	0.49
<b>Offset Length(Metric)</b>	12.5
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Width W (Imperial)</b>	0.20
<b>Width W (Metric)</b>	5.1
<b>Bundle Diameter Min (Imperial)</b>	0.08
<b>Bundle Diameter Min (Metric)</b>	2.0
<b>Bundle Diameter Max (Imperial)</b>	1.97

<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Thickness T (Metric)</b>	1.5
<b>Height H (Imperial)</b>	0.60
<b>Height H (Metric)</b>	16.1
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.24
<b>Panel Thickness Min (Metric)</b>	0.50
<b>Panel Thickness Max (Metric)</b>	6.65
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.27
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.27
<b>Mounting Hole Diameter D Max (Metric)</b>	6.9
<b>Disc Diameter(Metric)</b>	16.6
<b>Disc Diameter (Imperial)</b>	0.65
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut**

PA66HIRHS

**Material Cable Tie**

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +230°F (-40°C to +110°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

3000

**Package Quantity (Metric)**

3000

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.