

Specification Sheet

Part Number: 169-60022



Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 100 ft/pkg

| | |
|--------------------------------|---|
| Article Number | 169-60022 |
| Type | CTN140 |
| Color | Black with Gray Stripe (BKSTGY) |
| Features & Benefits | <ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight |
| Quantity Per | box |

Product Description

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 100 ft/pkg

Global Part Name

CTN140-PA6-BK

Technical Description

Convoluted Tubing, Slit, 1/4" Dia., PA6, Black w/Gray Stripe

Length L (Imperial)

100.0

Length L (Metric)

30.5

Inner Diameter D (Imperial)

0.276

Inner Diameter D (Metric)

7.01

Diameter D (imperial)

0.398

Diameter D (metric)

10.11

Outside Diameter OD(Imperial)

0.398

Outside Diameter OD(metric)

10.11

Nominal Diameter (Imperial)

0.25

Nominal Diameter (Metric)

6.35

| | |
|---------------------------------------|-----------------------------------|
| Wall Thickness WT (Imperial) | .004 |
| Wall Thickness WT (Metric) | 0.102 |
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |
| Flammability | UL 94 HB |
| Halogen free | No |
| Operating Temperature (Metric) | -40°F to +300°F (-40°C to +149°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3926909987 |

