



- NOTES:
- 1) USE WITH T18 THRU T50 CABLE TIES
 - 2) MOUNTING HOLE Ø .188
 - 3) MOUNTING HOLE MINIMUM DEPTH 1.000

HeilmannTyton

ALL DIMENSIONS SHOWN IN THIS DRAWING ARE EXCLUSIVE PROPERTY OF HEILMANN TYTON

DATE	REV	BY	CHKD

DESIGNED BY	DATE	BY	CHKD
SAUL	4/7/98		
PART NO.			
A			

TOLERANCES	UNITS
.XXX ± .0000	INCHES
.XXX ± .000	
.XXX ± .01	
.X ± .03	
∠ = ± 0.5°	
OTHER SPECIFIC SPECIFICS	

NUMBER	NAME	DESCRIPTION
MIMB0	MIMB0	NYLON 6/6 HIGH IMPACT BLACK
MIMB0	MIMB0	MASONRY MOUNT

REV	DATE	BY	CHKD
1	07/17/93		
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			